

Izdelek / Product: **JUBIZOL FINISH S 1.0**

**IZJAVA O LASTNOSTIH**  
**DECLARATION OF PERFORMANCE**  
**Št. / No. 001/19-JZF**

1. **Enotna identifikacijska oznaka tipa proizvoda / Unique identification code of product**  
 10.02.29

2. **Predvidena uporaba / Intended use**

**Siloksaniziran akrilni glajen omet za obdelavo špalet in okrasnih robov /  
 Siloxane acrylic smooth render finish for reveals and decorative facade elements**

3. **Proizvajalec / Manufacturer**

JUB d.o.o.  
 Dol pri Ljubljani 28  
 SI-1262 Dol pri Ljubljani  
 Slovenia  
[www.jub.eu](http://www.jub.eu)

4. **Sistemi ocenjevanja in preverjanja nespremenljivosti lastnosti / System of AVCP**

Sistem 3 / System 3

5. **Tehnična specifikacija / Technical specification**

EN 15824:2017

6. **Navedene lastnosti / Declared performance**

Bistvene značilnosti / Characteristic	Lastnost / Declaration	Standard / Norm	Tehnična specifikacija / Technical specification
Odziv na ogenj / Reaction to fire	<b>A2</b>	EN 13501-1	EN 15824:2017
Sprijemna trdnost / Bond strength	<b>&gt; 0,3 MPa</b>	EN 1542	EN 15824:2017
Toplotna prevodnost $\lambda_{10, \text{suh}}$ / Thermal conductivity $\lambda_{10, \text{dry}}$	<b>0,83 W/mK, P=50%</b>	EN 1745	EN 15824:2017
Paroprepusnost / Water vapour permeability	<b>V1 (visoka) / V1 (High)</b>	EN ISO 7783-2	EN 15824:2017
Vpijanje vode / Water absorption	<b>W3</b>	EN 1062-3	EN 15824:2017



7. **Proizvod je tudi komponenta zunanjega toplotnoizolacijskega sistema z ometom /**  
*Product is also component of external thermal insulation composite system with render*

**JUBIZOL EPS, ETA-09/0393**  
**JUBIZOL PB EPS, ETA-13/0633**  
**JUBIZOL S70, ETA-08/0236**  
**JUBIZOL XPS, ETA-07/0028**

**ZAG Ljubljana 1404-CPR-2792**  
**ZAG Ljubljana 1404-CPR-3215**  
**ZAG Ljubljana 1404-CPR-3222**  
**ZAG Ljubljana 1404-CPR-2794**

**Lastnosti proizvoda, navedenega zgoraj, so v skladu z navedenimi lastnostmi. Za izdajo te izjave o lastnostih je v skladu z Uredbo (EU) št. 305/2011 odgovoren izključno proizvajalec, naveden zgoraj.**

*The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.*

**Podpisal za in v imenu proizvajalca / Signed for and on behalf of the manufacturer by:**

Dol pri Ljubljani, 17.12.2019

Danijel Lisičić,  
Vodja razvojnega področja



JUB d.o.o.  
Dol pri Ljubljani 28  
SI-1262 Dol pri Ljubljani, Slovenija

2



<b>CE</b>	
17	
JUB d.o.o. Dol pri Ljubljani 28 SI – 1262 Dol pri Ljubljani Slovenia	
Unique identification code of product: 10.02.29 Declaration of performance No.: 001/19-JZF	
<b>EN 15824:2017</b> 1404	
<i>Siloxane acrylic smooth render finish for reveals and decorative facade elements</i>	
Reaction to fire	A2
Bond strength	> 0,3 MPa
Thermal conductivity $\lambda_{10,dry}$	0,83 W/mK, P = 50% (value from EN 1745)
Water vapour permeability	V1
Water absorption	W3
<a href="http://www.jub.eu">www.jub.eu</a>	